

## H2017

Payload:	20 kg.
Rækkevidde:	1.700 mm.
Vægt:	72 kg.
Gentagelsesnøjagtighed:	±0,1 mm.
Temperatur:	0 - 45°C
Indbygning:	Gulv
IP-klasse:	IP 54
I/O Power:	DC 24 V / Max. 3 A

## BEVÆGELSE (PER LED/HASTIGHED)

J1	±360° / 100° /s
J2	±125° / 80° /s
J3	±160° / 100° /s
J4	±360° / 180° /s
J5	±360° / 180° /s
J6	±360° / 180° /s

## CONTROLLER

Interface:	Serial (RS232) / USB 3.0 (RS422/485*), TCP/IP (* Requires a USB to RS422/485 converter)
Fieldbus**:	Modbus-TCP (Master/Slave) / Modbus-RTU (Master)/ EtherNet/IP (Adapter) / PROFINET IO (Device) (**Install a gateway for other communication support)
Dimension:	490 x 390 x 287 mm
Vægt:	13 kg.
IP-klasse:	IP 30
Digital I/O:	16 / 16
Analog I/O:	2 / 2
I/O Power:	DC 24 V
Strøm:	100~240 VAC, 50~60Hz
Kabellængde, (arm):	6,0 meter

## TEACH PENDANT

IP-klasse:	IP 40
Dimension:	264 x 218 x 42 mm.
Skærm størrelse / vægt:	10,1" / 0,8 kg.
Kabellængde, (skærm):	4,5 meter